Freestanding Pedestals
Models: SOSPF_20, SOSPF_20L, SOSPF_20R

Mobile Pedestals
Models: SOSPM_20, SOSPM_20L, SOSPM_20R

Stretch Freestanding Pedestals
Models: SOSSF_#

Stretch Mobile Pedestals
Models: SOSSM_#

Stretch Mobile Pedestals
Models: SOSSM_#

Mobile Work Carts
Models: SOSWC_20

Cushions
Model: SKSAC

Felt Box
Model: SOSSFB

Freestanding, Mobile, Stretch Freestanding, Stretch Mobile Pedestals & Mobile Work Cart Dimensions

Overall Depth	SOSPF_20, SOSPM_20, SOSSF_#, SOSSM_#, SOSWC_20	20 in / 508 mm
Overall Width	SOSWC_20	14 in / 356 mm
	SOSPF_20, SOSPF_20L, SOSPF_20R, SOSPM_20, SOSPM_20L, SOSPM_20R	15.5 in / 394 mm
	SOSSF_30, SOSSM_30	30 in / 762 mm
	SOSSF_36, SOSSM_36	36 in / 914 mm
	SOSSF_42, SOSSM_42	42 in / 1067 mm
	SOSSF_48, SOSSM_48	48 in / 1219 mm
Overall Height	SOSPF_20, SOSPF_20L, SOSPF_20R, SOSSF_##	17.38 in / 442 mm
	SOSWC_20	19 in / 483 mm
	SOSPM_20, SOSPM_20L, SOSPM_20R, SOSSM_##	19.5 in / 495 mm
Overall Weight	SOSPF_20, SOSPM_20	83.69-117.85 lbs. / 38-53.5 kg
	SOSSF_##, SOSSM_##	120.59-206.76 lbs. / 55-94 kg
	SOSWC_20	170-198 lbs. / 77-90 kg
Shipping Cube	SOSPF_20, SOSPM_20	2.92 ft³ / 0.082 m³
	SOSSF_##, SOSSM_##	5.65-9.03 ft³ / 0.16-0.25 m³
	SOSWC_20	1.99-2.29 ft³ / 0.056-0.064 m³

Cushion Dimensions

Overall Depth	SKSAC1219	12 in / 305 mm
	SKSAC20##	20 in / 508 mm
Overall Width	SKSAC2016	14 in / 356 mm
	SKSAC2018	18 in / 457 mm
	SKSAC1219	19 in / 483 mm
	SKSAC2024	24 in / 610 mm
	SKSAC2030	30 in / 762 mm
	SKSAC2036	36 in / 914 mm
	SKSAC2042	42 in / 1067 mm
	SKSAC2048	48 in / 1219 mm
Overall Height	SKSAC1219, SKSAC20##	1.5 in / 38 mm
Overall Weight	SKSAC1219, SKSAC20##	4-7 lbs. /1.8-3 kg
Shipping Cube	SKSAC1219, SKSAC20##	0.40-0.74 ft³ / 0.011-0.021 m³



SOSPFBB20
Leveler adjustment 0.75 in



SOSPMBB20
Caster height - 2.3 in



SOSSFCRBB30



SOSSMLBBC30



SOSWCOF20



SOSWCOF20



SOSWCDLF20
SKSAC1219 (Cushion)

Felt Box Dimensions

Overall Depth	SOSSFB	9.25 in / 235 mm
Overall Width	SOSSFB	13.7 in / 235 mm
Overall Height	SOSSFB	10 in / 254 mm
Overall Weight	SOSSFB	12.25 lbs. / 5.6 kg
Shipping Cube	SOSSFB	0.73 ft³ / 0.020 m³

Contact sales representative for more information.

Features

- 100% Canadian made
- 1 in (25 mm) thick high performance thermally fused laminate tops
- Top overlay construction; 1 in (25 mm) thick side and bottom panels, 0.75 in (19 mm) thick back panels and drawer and/or door fronts
- Box/Box drawer pedestals are equipped with premium full extension ball bearing drawer slides
- Hinged doors are equipped with soft close 103° overlay hinges
- Die cast aluminum handles where applicable, 8 in (203 mm) wide with 7.6 in (192 mm) center to center drilling
- Drawers and doors are all key locking
- Freestanding units have leveling glides with 0.75 in (19 mm) adjustability
- Mobile pedestals have four locking 2.5 in height casters
- All storage within the series ships assembled

MODELS: SOSPF_20, SOSPF_20L, SOSPF_20R, SOSPM_20, SOSPM_20L, SOSPM_20R

- Freestanding and mobile units available with Box/Box and Door configurations
- Door configuration inside dimensions 13.5 in (343 mm) wide x 12.5 in (318 mm) height

MODELS: SOSSF_#, SOSSM_#

- Freestanding and mobile units available with Box/Box/Cubby, Cubby/Box/Box, Door hinge left and right /Cubby configurations
- 30 in (762 mm) wide units have a 15 in (381 mm) wide pedestal and 15 in (381 mm) wide cubby. Interior dimensions 14.25 in (362 mm) wide x 12.5 in (318 mm) height
- 36 in (914 mm) wide units have a 18 in pedestal
- 42 in (1067 mm) wide units have a 24 in pedestal
- 48 in (1219 mm) wide units have a 30 in pedestal
- 36 in (914 mm) to 48 in (1219 mm) wide units have a 18 in (457 mm) wide cubby. Interior dimensions 17.25 in (438 mm) wide x 12.5 in (318 mm) height

MODELS: SOSWC_20

- Configurations include open, door hinged left, and door hinged right, with and without PET felt wrap arounds and cushion tops
- Open units inside dimensions 12 in (305 mm) wide x 13 in (330 mm) height
- Carts have two locking casters (on the user side) and two wheels with a diameter of 5.25 in (133 mm). Rubber friction trim suitable for both hard and carpeted surfaces
- ADA compliant, die cast aluminum D (shape) handles, 7.874 in (200 mm) wide with 7.559 in (192 mm) center-to-center drilling
- Handles are compatible with original Office Spaces die-cast pulls; order separately as replacements
- PET Felt extends 2 in (51 mm) past the top of the mobile work cart

MODELS: SKSAC2016

- Cushion for freestanding and mobile pedestals
- Cushion core: V145 High-Density Foam (HDF) | Density: 1.5-1.8 lbs./ft³

MODELS: SKSAC1219

- Cushion for mobile work carts
- Cushion core: V145 High-Density Foam (HDF) | Density: 1.5-1.8 lbs./ft³

MODELS: SOSSFB

- Felt box for mobile work cart cubby

Options

- Wood grain or solid laminate finishes available for tops, chassis and doors/drawers in an array of standard finishes
- Select top finish, top edge finish, chassis finish and door/drawer finish separately
- Door, drawer handles & mobile work cart wheels are available in a broad range of highly durable metal powder coat paint finishes
- PET Felt wrap, where applicable, is 0.35 in (9 mm) thick and available in an array of standard colors

Construction

- Glue and dowel case construction
- 1 in (25mm) thick high performance thermally fused laminate tops with 0.12 in (3 mm) thick PVC edge band, 45 lbs. density particleboard core.
- Chassis sides are 1 in (25 mm), back panel is 0.75 in (19.05 mm) and bottom 1 in (25 mm) thick high perfomance thermally fused laminate, 45 lbs. density particleboard
- PET Felt surrounds-9 mm thick material

Warranty
Lifetime warranty on all components, except the following:
- 5 year warranty on foam, PET felt and textiles

Environmental
View Environmental Data Sheets online.

Awards/Certifications
- Meets or exceeds all applicable ANSI/BIFMA X5.9 2019, X5.5-2021 standards for safety and durability
- Greenguard and Greenguard Gold
- TSCA Title VI compliant, CAL Prop 65 Carb compliant
- ANSI/BIFMA e3-2019 LevelTM3 certified
- Manufactured in ISO 9001 and 14001 certified facilities

Please visit globalfurnituregroup.com for additional product information including industry and environmental certifications.