# **ATWPOP236** | application typical | Open Spaces

## Bill of materials

**8/7/2026**

| Line | Cat | Qty | Part Number | | |
|---|---|---|---|---|---|
| 1 | GUS | 4 | **6075** | Ext Weight (lbs) | 0.00 |
| | | | Uphostered Back, Weight Sensing Synchro-Tilter, Std with Arms, Std with Nylon Base. Std with 2.5" Casters. NOETIC | Ext Volume (Ft3) | 0.00 |
| 2 | GCU | 4 | **SCTAH** | Ext Weight (lbs) | 0.00 |
| | | | Table Mounted Bag Hook for Use on Tables, COLLABORATIVE SPACES | Ext Volume (Ft3) | 0.00 |
| 3 | GCU | 2 | **SOAFPS2148** | Ext Weight (lbs) | 5.66 |
| | | | 47.50"w x 21"h, Felt Beam Mounted Privacy Screen, Can be Mounted Anywhere Along the Beam, OPEN SPACES | Ext Volume (Ft3) | 2.30 |
| 4 | GCU | 1 | **SOEE8BF0121** | Ext Weight (lbs) | 2.82 |
| | | | Basefeed Kit, Kit Consists of Bracket + Cover + Basefeed, Attaches Inside of Leg, Used w/27" Beam, OPEN SPACES | Ext Volume (Ft3) | 0.05 |
| 5 | GCU | 2 | **SOEE8D1** | Ext Weight (lbs) | 0.20 |
| | | | Circuit #1, Black Duplex Receptacle, Utility Circuit, Snaps into Power Distribution Housing, OPEN SPACES | Ext Volume (Ft3) | 0.02 |
| 6 | GCU | 2 | **SOEE8D2** | Ext Weight (lbs) | 0.20 |
| | | | Circuit #2, Black Duplex Receptacle, Utility Circuit, Snaps into Power Distribution Housing, OPEN SPACES | Ext Volume (Ft3) | 0.02 |
| 7 | GCU | 2 | **SOEE8DA** | Ext Weight (lbs) | 0.20 |
| | | | Circuit #A, Black Duplex Receptacle, Dedicated Circuit, Snaps into Power Distribution Housing, OPEN SPACES | Ext Volume (Ft3) | 0.02 |
| 8 | GCU | 2 | **SOEE8DB** | Ext Weight (lbs) | 0.20 |
| | | | Circuit #B, Black Duplex Receptacle, Dedicated Circuit, Snaps into Power Distribution Housing, OPEN SPACES | Ext Volume (Ft3) | 0.02 |
| 9 | GCU | 1 | **SOEE8JC28** | Ext Weight (lbs) | 1.00 |
| | | | 28", Jumper Cable, Connects Two Beams at an Inline Connection, OPEN SPACES | Ext Volume (Ft3) | 1.17 |
| 10 | GCU | 2 | **SOEE8PDH48** | Ext Weight (lbs) | 3.24 |
| | | | 48" Power Distrubution Housing, OPEN SPACES | Ext Volume (Ft3) | 3.30 |
| 11 | GCU | 2 | **SOILB48** | Ext Weight (lbs) | 27.20 |
| | | | 7"h x 48"w, Inline/End Leg Beam, Inline Connection on One End & End Leg Connection on Other End, OPEN SPACES | Ext Volume (Ft3) | 1.16 |
| 12 | GCU | 2 | **SOLEB27** | Ext Weight (lbs) | 8.10 |
| | | | 27"h x 18"w, End Leg, Includes End Cap, End Leg Supports a Beam with an End Leg Connection at One or Two Ends, OPEN SPACES | Ext Volume (Ft3) | 2.02 |
| 13 | GCU | 1 | **SOLMT27** | Ext Weight (lbs) | 3.92 |
| | | | 27"h x 18"w, Mid T Leg, Supports a Beam Between Two Inline Beams at an Inline Connection, OPEN SPACES | Ext Volume (Ft3) | 1.51 |
| 14 | GCU | 2 | **SOSWCDRF20** | Ext Weight (lbs) | 396.00 |
| | | | 20"d x 14"w x 19"h, Mobile Work Cart, Right Hinged Door w/Felt Wrap Around, OPEN SPACES | Ext Volume (Ft3) | 3.98 |
| 15 | GCU | 4 | **SOSWFSC2448** | Ext Weight (lbs) | 142.32 |
| | | | 24"d x 48"w x 1"h, Rectangular Semi-Supported Fixed Height Worksurface w/Scoop, Supported by Brackets on 1 End & Legs on | Ext Volume (Ft3) | 2.60 |
| 16 | GCU | 2 | **SOSWFSL** | Ext Weight (lbs) | 8.98 |
| | | | 28"h, Left Single End Leg, Legs Cannot Be Used for Single Table, OPEN SPACES | Ext Volume (Ft3) | 0.72 |

# **ATWPOP236** | application typical | Open Spaces

## Bill of materials

**8/7/2026**

| Line | Cat | Qty | Part Number | | |
|---|---|---|---|---|---|
| 17 | GCU | 2 | **SOSWFSR** | Ext Weight (lbs) | 8.98 |
| | | | 28"h, Right Single End Leg, Legs Cannot Be Used for Single Table, OPEN SPACES | Ext Volume (Ft3) | 0.72 |
| 18 | GCU | 2 | **SOSWFSS** | Ext Weight (lbs) | 11.14 |
| | | | 28.5"h, Shared Leg for Worksurfaces, OPEN SPACES | Ext Volume (Ft3) | 1.22 |
| 19 | GCU | 8 | **SOSWHAS48** | Ext Weight (lbs) | 26.24 |
| | | | 2"d x 30"w x 1.75"h, HAT Channel for Fixed Height Worksurfaces, Black Only, OPEN SPACES | Ext Volume (Ft3) | 0.48 |
| 20 | GCU | 8 | **SOSWSP** | Ext Weight (lbs) | 3.52 |
| | | | Worksurface Support Bracket, 36" - 54" Tops 2 Brackets, 60" - 84" Tops 3 Brackets, 4 Brackets May be Used to Avoid Scallop, Fits | Ext Volume (Ft3) | 0.16 |