ATWPOP245 | application typical | Open Spaces

Bill of materials

08-07-2026

Line	Cat	Qty	Part Number		
1	GUS	2	**6075**	Ext Weight (lbs)	0.00
			Uphostered Back, Weight Sensing Synchro-Tilter, Std with Arms, Std with Nylon Base. Std with 2.5" Casters. NOETIC	Ext Volume (Ft3)	0.00
2	GCU	2	**SCTACT**	Ext Weight (lbs)	0.00
			PET Felt Wire Manager, COLLABORATIVE SPACES	Ext Volume (Ft3)	0.00
3	GCU	2	**SCTAPEA**	Ext Weight (lbs)	0.00
			Nik Edge/Clamp Mount Power Module, 1 AC / 2 USB, COLLABORATIVE SPACES	Ext Volume (Ft3)	0.00
4	GCU	2	**SKSLCHFH2066**	Ext Weight (lbs)	308.66
			20"d x 66"w x 14"h, Low Storage, 18" Hinged Door w/Leg Grommet, 30" File Drawer, 18" Hinged Door w/Leg Grommet,	Ext Volume (Ft3)	20.68
5	GCU	2	**SKSLU2066**	Ext Weight (lbs)	33.36
			20"d x 66"w x 6"h, Low & High Storage Undercarriage w/Legs, Can be used on Single Units of the Same Size or a Combo of Low/High	Ext Volume (Ft3)	9.16
6	GCU	1	**SKWARPL2366D24**	Ext Weight (lbs)	5.06
			21"d x 41.8"w x 23"h, Left Curved Privacy Panel, Must be used on the Opposite Side of the Credenza, OFFICE SPACES	Ext Volume (Ft3)	2.64
7	GCU	1	**SKWARPR2366D24**	Ext Weight (lbs)	5.06
			21"d x 41.8"w x 23"h, Right Curved Privacy Panel, Must be used on the Opposite Side of the Credenza, OFFICE SPACES	Ext Volume (Ft3)	2.64
8	GCU	2	**SKWESCT**	Ext Weight (lbs)	0.78
			Storage Cable Tube, Black Only, Aligns Between the Surface and Grommet on the Lower Storage Unit, Capacity 4 Wires, OFFICE	Ext Volume (Ft3)	0.10
9	GCU	4	**SKWSDC66**	Ext Weight (lbs)	15.88
			2"d x 36"w x 1.75"h, HAT Channel for Worksurfaces, Black Only, OFFICE SPACES	Ext Volume (Ft3)	0.28
10	GCU	2	**SKWSHA3C18T24**	Ext Weight (lbs)	243.94
			Height Adjustable 3 Column Kit, For 18"d or 24"d Surfaces, Used w/Storage on 1 Side, OFFICE SPACES	Ext Volume (Ft3)	50.80
11	GCU	1	**SKWSRBL1842**	Ext Weight (lbs)	23.82
			18"d x 42"w x 1"h, Left Return w/Radius at Bottom Left, Require Return HAT Channel, OFFICE SPACES	Ext Volume (Ft3)	0.44
12	GCU	1	**SKWSRBR1842**	Ext Weight (lbs)	23.82
			18"d x 42"w x 1"h, Right Return w/Radius at Bottom Right, Require Return HAT Channel, OFFICE SPACES	Ext Volume (Ft3)	0.44
13	GCU	2	**SKWSRDC42**	Ext Weight (lbs)	7.28
			8.5"d x 24"w x 1.75"h, HAT Channel for Return Worksurfaces, Includes 1 Support Bracket, Black Only, OFFICE SPACES	Ext Volume (Ft3)	0.42
14	GCU	2	**SKWSRTRL2466**	Ext Weight (lbs)	98.62
			24"d x 66"w x 1"h, Rectangular Worksurface w/Radius on Top Left & Top Right, Unsupported 54â€□ or Up Require Support Channels,	Ext Volume (Ft3)	1.84
15	GCU	2	**SOAH72**	Ext Weight (lbs)	5.10
			70.685"w, Upper Frame Horizontal, OPEN SPACES	Ext Volume (Ft3)	0.10
16	GCU	2	**SOAHLL**	Ext Weight (lbs)	22.98
			Linear Light, 2 Lights Per Hood, Includes Starter/Daisy/Transformer & Basket, Cannot be Daisy Chained, Can Only Fit on Upper Frames	Ext Volume (Ft3)	1.86

ATWPOP245 | application typical | Open Spaces

Bill of materials

08-07-2026

Line	Cat	Qty	Part Number		
17	GCU	2	**SOAHPL**	Ext Weight (lbs)	6.44
			Hanging Planter, OPEN SPACES	Ext Volume (Ft3)	1.24
18	GCU	2	**SOAHTB4536**	Ext Weight (lbs)	15.98
			36"w x 39"h, Hanging Felt Tackboard, Sits Inside Bottom Channel of Beam, Choose Next Size Down to Fit onto the Upper Frame, OPEN	Ext Volume (Ft3)	1.22
19	GCU	1	**SOAVPD45NS**	Ext Weight (lbs)	3.15
			45"h, Vertical Post Middle, No Shelf Connection, OPEN SPACES	Ext Volume (Ft3)	0.35
20	GCU	2	**SOAVPS45NS**	Ext Weight (lbs)	6.18
			45"h, Vertical Post End, No Shelf Connection, OPEN SPACES	Ext Volume (Ft3)	0.46
21	GCU	1	**SOEE8BF0115**	Ext Weight (lbs)	2.25
			Basefeed Kit, Kit Consists of Bracket + Cover + Basefeed, Attaches Inside of Leg, Used w/21" Beam, OPEN SPACES	Ext Volume (Ft3)	0.03
22	GCU	1	**SOEE8D1**	Ext Weight (lbs)	0.10
			Circuit #1, Black Duplex Receptacle, Utility Circuit, Snaps into Power Distribution Housing, OPEN SPACES	Ext Volume (Ft3)	0.01
23	GCU	1	**SOEE8D2**	Ext Weight (lbs)	0.10
			Circuit #2, Black Duplex Receptacle, Utility Circuit, Snaps into Power Distribution Housing, OPEN SPACES	Ext Volume (Ft3)	0.01
24	GCU	1	**SOEE8DA**	Ext Weight (lbs)	0.10
			Circuit #A, Black Duplex Receptacle, Dedicated Circuit, Snaps into Power Distribution Housing, OPEN SPACES	Ext Volume (Ft3)	0.01
25	GCU	1	**SOEE8DB**	Ext Weight (lbs)	0.10
			Circuit #B, Black Duplex Receptacle, Dedicated Circuit, Snaps into Power Distribution Housing, OPEN SPACES	Ext Volume (Ft3)	0.01
26	GCU	1	**SOEE8JC28**	Ext Weight (lbs)	1.00
			28", Jumper Cable, Connects Two Beams at an Inline Connection, OPEN SPACES	Ext Volume (Ft3)	1.17
27	GCU	2	**SOEE8PDH72**	Ext Weight (lbs)	6.08
			72" Power Distrubution Housing, OPEN SPACES	Ext Volume (Ft3)	6.40
28	GCU	2	**SOILB72**	Ext Weight (lbs)	40.88
			7"h x 72"w, Inline/End Leg Beam, Inline Connection on One End & End Leg Connection on Other End, OPEN SPACES	Ext Volume (Ft3)	1.76
29	GCU	2	**SOLEB21L24**	Ext Weight (lbs)	7.74
			21"h x 24"w, End Leg, Includes End Cap, End Leg Supports a Beam with an End Leg Connection at One or Two Ends, OPEN SPACES	Ext Volume (Ft3)	1.64
30	GCU	1	**SOLMT21L24**	Ext Weight (lbs)	3.70
			21"h x 24"w, Mid T Leg, Supports a Beam Between Two Inline Beams at an Inline Connection, OPEN SPACES	Ext Volume (Ft3)	1.16