# **ATWPOP251** | application typical | Open Spaces

## Bill of materials

**8/5/2026**

| Line | Cat | Qty | Part Number | | |
|---|---|---|---|---|---|
| 1 | GUS | 6 | **6075** | Ext Weight (lbs) | 0.00 |
| | | | Uphostered Back, Weight Sensing Synchro-Tilter, Std with Arms, Std with Nylon Base. Std with 2.5" Casters. NOETIC | Ext Volume (Ft3) | 0.00 |
| 2 | GCU | 3 | **SOAH72** | Ext Weight (lbs) | 7.65 |
| | | | 70.685"w, Upper Frame Horizontal, OPEN SPACES | Ext Volume (Ft3) | 0.15 |
| 3 | GCU | 3 | **SOAHLL** | Ext Weight (lbs) | 34.47 |
| | | | Linear Light, 2 Lights Per Hood, Includes Starter/Daisy/Transformer & Basket, Cannot be Daisy Chained, Can Only Fit on Upper Frames | Ext Volume (Ft3) | 2.79 |
| 4 | GCU | 6 | **SOAHPL** | Ext Weight (lbs) | 19.32 |
| | | | Hanging Planter, OPEN SPACES | Ext Volume (Ft3) | 3.72 |
| 5 | GCU | 3 | **SOAHTB3942** | Ext Weight (lbs) | 23.70 |
| | | | 42"w x 33"h, Hanging Felt Tackboard, Sits Inside Bottom Channel of Beam, Choose Next Size Down to Fit onto the Upper Frame, OPEN | Ext Volume (Ft3) | 1.80 |
| 6 | GCU | 2 | **SOAVPD39NS** | Ext Weight (lbs) | 5.58 |
| | | | 39"h, Vertical Post Middle, No Shelf Connection, OPEN SPACES | Ext Volume (Ft3) | 0.60 |
| 7 | GCU | 2 | **SOAVPS39NS** | Ext Weight (lbs) | 5.44 |
| | | | 39"h, Vertical Post End, No Shelf Connection, OPEN SPACES | Ext Volume (Ft3) | 0.40 |
| 8 | GCU | 1 | **SOEE8BF0115** | Ext Weight (lbs) | 2.25 |
| | | | Basefeed Kit, Kit Consists of Bracket + Cover + Basefeed, Attaches Inside of Leg, Used w/21" Beam, OPEN SPACES | Ext Volume (Ft3) | 0.03 |
| 9 | GCU | 3 | **SOEE8D1** | Ext Weight (lbs) | 0.30 |
| | | | Circuit #1, Black Duplex Receptacle, Utility Circuit, Snaps into Power Distribution Housing, OPEN SPACES | Ext Volume (Ft3) | 0.03 |
| 10 | GCU | 3 | **SOEE8D2** | Ext Weight (lbs) | 0.30 |
| | | | Circuit #2, Black Duplex Receptacle, Utility Circuit, Snaps into Power Distribution Housing, OPEN SPACES | Ext Volume (Ft3) | 0.03 |
| 11 | GCU | 3 | **SOEE8DA** | Ext Weight (lbs) | 0.30 |
| | | | Circuit #A, Black Duplex Receptacle, Dedicated Circuit, Snaps into Power Distribution Housing, OPEN SPACES | Ext Volume (Ft3) | 0.03 |
| 12 | GCU | 3 | **SOEE8DB** | Ext Weight (lbs) | 0.30 |
| | | | Circuit #B, Black Duplex Receptacle, Dedicated Circuit, Snaps into Power Distribution Housing, OPEN SPACES | Ext Volume (Ft3) | 0.03 |
| 13 | GCU | 2 | **SOEE8JC28** | Ext Weight (lbs) | 2.00 |
| | | | 28", Jumper Cable, Connects Two Beams at an Inline Connection, OPEN SPACES | Ext Volume (Ft3) | 2.34 |
| 14 | GCU | 3 | **SOEE8PDH72** | Ext Weight (lbs) | 9.12 |
| | | | 72" Power Distrubution Housing, OPEN SPACES | Ext Volume (Ft3) | 9.60 |
| 15 | GCU | 6 | **SOHAFE2C30T36** | Ext Weight (lbs) | 92.34 |
| | | | 25"-51.2"h, Height Adjustable Base Extended Range, Used w/30"d - 36"d Surfaces, Includes Controller & Handset, Does not Incude HAT | Ext Volume (Ft3) | 92.34 |
| 16 | GCU | 2 | **SOILB72** | Ext Weight (lbs) | 40.88 |
| | | | 7"h x 72"w, Inline/End Leg Beam, Inline Connection on One End & End Leg Connection on Other End, OPEN SPACES | Ext Volume (Ft3) | 1.76 |

# **ATWPOP251** | application typical | Open Spaces

## Bill of materials

**8/5/2026**

| Line | Cat | Qty | Part Number | | |
|---|---|---|---|---|---|
| 17 | GCU | 1 | **SOINB72** | Ext Weight (lbs) | 20.26 |
| | | | 7"h x 72"w, Inline/Inline Beam, Inline Connections on Both Ends, OPEN SPACES | Ext Volume (Ft3) | 0.88 |
| 18 | GCU | 2 | **SOLEB21L24** | Ext Weight (lbs) | 7.74 |
| | | | 21"h x 24"w, End Leg, Includes End Cap, End Leg Supports a Beam with an End Leg Connection at One or Two Ends, OPEN SPACES | Ext Volume (Ft3) | 1.64 |
| 19 | GCU | 2 | **SOLMT21L24** | Ext Weight (lbs) | 7.40 |
| | | | 21"h x 24"w, Mid T Leg, Supports a Beam Between Two Inline Beams at an Inline Connection, OPEN SPACES | Ext Volume (Ft3) | 2.32 |
| 20 | GCU | 6 | **SOSWCDL20** | Ext Weight (lbs) | 1,110.00 |
| | | | 20"d x 14"w x 19"h, Mobile Work Cart, Left Hinged Door, OPEN SPACES | Ext Volume (Ft3) | 13.74 |
| 21 | GCU | 12 | **SOSWHAT72** | Ext Weight (lbs) | 47.64 |
| | | | 2"d x 36"w x 1.75"h, HAT Channel for Heigth Adjustable Worksurfaces, Black Only, OPEN SPACES | Ext Volume (Ft3) | 0.84 |
| 22 | GCU | 6 | **SOWHSR2970** | Ext Weight (lbs) | 401.52 |
| | | | 29"d x 70"w x 1"h, Rectangular Freestanding Worksurface w/Small Radius Corners, Used w/Height Adjustable Base or Fixed Height Leg | Ext Volume (Ft3) | 7.50 |