chap seating | product specification

Guest Seating
Models: 1002, 1003, 1010, 1011, 1014, 1015

Dimensions (Models: 1002, 1003, 1010, 1011, 1014, 1015)

Overall Length	1002, 1003	24.5 in / 622 mm
	1010, 1011, 1014, 1015	25 in / 635 mm
Overall Width	1002, 1003	24.5 in / 622 mm
	1010, 1011, 1014, 1015	25.5 in / 648 mm
Overall Height	1002, 1003	30 in / 762 mm
	1010, 1014	31 in / 787 mm
	1011, 1015	31.5 in / 800 mm
Seat Depth		20 in / 508 mm
Seat Width	1002, 1003	22 in / 559 mm
	1010, 1011, 1014, 1015	21 in / 533 mm
Seat Height		18 in / 457 mm
Back Height - From Seat	1002, 1003	12.5 in / 318 mm
	1010, 1011, 1014, 1015	13.5 in / 343 mm
Armrest Clearance		20 in / 508 mm
Arm Height - From Seat	1002, 1003	9 in / 229 mm
	1010, 1011, 1014, 1015	7.5 in / 191 mm
Product Weight	1002	27 lb / 12.2 kg
	1003	28 lb / 12.7 kg
	1010, 1011, 1014, 1015	21 lb / 9.5 kg
Shipping Cube	1002, 1003	13.25 ft³ / 0.38 m³
	1010, 1011, 1014, 1015	15.75 ft³ / 0.45 m³

Contact sales representative for more information.

Features

- Wood frame armchair

MODELS: 1003, 1010, 1014

- Horizontal wood slat back

MODELS: 1002, 1011, 1015

- Fully upholstered back

MODELS: 1010, 1011, 1014, 1015

- Flat back shape

MODELS: 1002, 1003

- Rounded back shape

Options

MODELS: 1010, 1011, 1014, 1015

- Frame available in 17 wood finishes

MODELS: 1002, 1003

- No custom wood finishes will be considered for round back models (English Oak only)

Construction (Frame)

- Beechwood frame, legs and armrests

Construction (Glides)

- Standard white, non-marking, glides

Upholstery

- Can be upholstered in fabric, vinyl or leather



1003



1011



1014



1015

Foam (Seat)
- Seat cushion is 2.5 in (64 mm) thick
- Density: 1.8 lb, ILD: 50

Foam (Back)
MODELS: 1002, 1011, 1015
- Back foam is 1 in (25 mm) thick
- Density: 1.8 lb, ILD: 50

MODLES: 1003, 1010, 1014
- No back foam

Weight Capacity
Designed with an active weight capacity of 300 lb.

Warranty
Lifetime warranty on all components except the following:
- 5 year warranty on foam and textiles
- Warranty applies only to single shift, standard commercial usage (8 hours/day, 5 days/week)

Fire Rating
All foam and textiles are tested and certified, meeting California Technical Bulletin 117 (CAL TB 117-2013) standards.

Environmental
View Environmental Data Sheets online.
All foam is produced without using any ozone depleting chloro-flouro chemicals.

Awards/Certifications
- Meets or exceeds all applicable BIFMA standards for safety and durability
- Manufactured in ISO 9001 and 14001 certified facilities

Please visit globalfurnituregroup.com for additional product information including environmental certifications.