rambler ottomans | product specification

Lounge Seating
Models: RA2222SQ, RA2626SQ, RA3939SQ, RA2639RE, RA2652RE, RA2626TR, RA2639TR, RA2652TR

Dimensions
Square Ottomans (Models: RA2222SQ, RA2626SQ, RA3939SQ)

Overall Depth and Width	RA2222SQ	22.5 in / 572 mm
	RA2626SQ	26.5 in / 673 mm
	RA3939SQ	39.5 in / 1003 mm
Overall Height	with 1 in legs	15.5 in / mm
	with 3 in legs or casters	17.5 in / 445 mm
Product Weight	RA2222SQ	28 lbs. / 12.7 kg
	RA2626SQ	38.4 lbs. / 17.5 kg
	RA3939SQ	63 lbs. / 28.6 kg
Shipping Cube	RA2222SQ	6.5 ft³ / 0.18 m³
	RA2626SQ	9.5 ft³ / 0.27 m³
	RA3939SQ	19.5 ft³ / 0.55 m³

Rectangle Ottomans (Models: RA2639RE, RA2652RE)

Overall Depth		26.5 in / 673 mm
Overall Width	RA2639RE	39.5 in / 1003 mm
	RA2652RE	52.5 in / 1334 mm
Overall Height	with 1 in legs	15.5 in / 394 mm
	with 3 in legs or casters	17.5 in / 445 mm
Product Weight	RA2639RE	57.4 lbs. / 26.1 kg
	RA2652RE	64 lbs. / 29.1 kg
Shipping Cube	RA2639RE	13.75 ft³ / 0.39 m³
	RA2652RE	17.75 ft³ / 0.50 m³

Trapazoid Ottomans (Models: RA2626TR, RA2639TR, RA2652TR)

Overall Depth	RA2626TR	27.5 in / 699 mm
	RA2639TR, RA2652TR	26.5 in / 673 mm
Overall Width	RA2626TR	27.5 in / 699 mm
	RA2639TR	39.5 in / 1003 mm
	RA2652TR	52.5 in / 1334 mm
Overall Height	with 1 in legs	15.5 in / 394 mm
	with 3 in legs or casters	17.5 in / 445 mm
Product Weight	RA2626TR	31.8 lbs. / 14.5 kg
	RA2639TR	48 lbs. / 21.8 kg
	RA2652TR	59.4 lbs. / 27.0 kg
Shipping Cube	RA2626TR	9.5 ft³ / 0.27 m³
	RA2639TR	13.75 ft³ / 0.39 m³
	RA2652TR	17.75 ft³ / 0.50 m³

Contact sales representative for more information.
Width and depth may vary by up to 0.5 in (13 mm).



RA2626SQ



RA2652RE



RA2626TR



RA2652TR

Features
- Ottomans with softened shapes
- Stationary legs or mobile casters available
- Several shapes allowing for a wide variety of configurations for education, office or heathcare environments
- Models do not gang
- Ships fully assembled

Options
- Legs are available in two finish colors: Night or Sand
- Casters can substitute for legs. Carpeted surface (universal) casters or hard surface casters are available
- Glide options:
  - White, non-marking, nylon glides are recommended for most flooring
  - Stainless steel cushioned glides are recommended for carpet or rubber flooring
  - Glides with felt pads are recommended for vinyl, cork or laminate flooring
  - Glides with rubber pads are non-slip. They are recommended for vinyl, hardwood, laminate, stone or ceramic flooring
- Moisture barrier option

COM Yardage

Yardage is based on unmatched materials with widths of 54 in for seating (standard seat size shown)

MODELS: RA2222SQ, RA2626SQ
- Top: 0.75 yards
- Sides: 1.00 yards
- Full Unit: 1.75 yards

MODEL: RA3939SQ
- Top: 1.25 yards
- Sides: 2.25 yards
- Full Unit: 3.50 yards

MODELS: RA2639RE, RA2652RE, RA2639TR, RA2652TR
- Top: 1.00 yards
- Sides: 1.50 yards
- Full Unit: 2.50 yards

MODELS: RA2626TR
- Top: 0.75 yards
- Sides: 1.50 yards
- Full Unit: 2.25 yards

Infection Control
- No Velcro
- Moisture barrier option
- For proper cleaning and disinfecting practices, the textile selection needs to be identified. It is vital that following any chemical application a clear water wipe down occur to avoid chemical build up that will lead to deterioration of the textile. Contact Global should information on using a specific disinfectant be required

On Site Repair and Replacement
- Legs and casters are removable and replaceable

Construction (Body)
- Interlocking puzzle box construction
- Underside is covered with fabric lining
- Metal-to-metal connections between all components
- 0.75 in (19 mm) thick fiberboard frame

Construction (Legs)
- Polypropylene legs
- 3 in (76 mm) or 1 in (25 mm) high

Upholstery
- Ottomans can be upholstered in fabric, coated textile or leather
- Top and sides can by upholstered in contrasting textiles (combining different material types is not recommended)

Foam
- Molded foam seat, 2.25 in (57 mm) thick
- Side foam is 1.25 in (32 mm). Density: 1.9 lbs., ILD: 50

Weight Capacity
- Designed with an active weight capacity of 300 lbs., under standard use (up to 8 hours/day, 5 days/week)

Warranty

Lifetime warranty on all components except the following:
- 5 year warranty on foam and textiles

Fire Rating

All foam and textiles are tested and certified, meeting California Technical Bulletin 117 (CAL TB 117-2013) standards.

Environmental

View Environmental Data Sheets online.

All foam is produced without using any ozone depleting chloro-flouro chemicals.

Awards/Certifications
- Meets or exceeds all applicable BIFMA standards for safety and durability
- Manufactured in ISO 9001 and 14001 certified facilities

Please visit globalfurnituregroup.com for additional product information including industry and environmental certifications.