prefer seating | product specification

Work Chairs and Stools
Models: 8458, 8459, 8458S, 8459S

Task Chair Dimensions (Models: 8458, 8459)

Overall Depth	24 in / 610 mm
Overall Width	25.5 in / 648 mm
Overall Height	37-41 in / 940-1041 mm
Seat Depth	18.5 in / 470 mm
Seat Width	19.75 in / 502 mm
Seat Height	18-22 in / 457-559 mm
Back Height - From Seat	19 in / 483 mm
Armrest Clearance	21.5 in / 546 mm
Arm Height - From Seat	8.5 in / 216 mm
Product Weight	26 lb / 11.8 kg
Shipping Cube	9.5 ft³ / 0.27 m³

Drafting Stool Dimensions (Models: 8458S, 8459S)

Overall Depth	24 in / 610 mm
Overall Width	25.5 in / 648 mm
Overall Height	42.5-50.5 in / 1080-1283 mm
Seat Depth	18.5 in / 470 mm
Seat Width	19.75 in / 502 mm
Seat Height	23.5-31.5 in / 597-800 mm
Back Height - From Seat	19 in / 483 mm
Armrest Clearance	21.5 in / 546 mm
Arm Height - From Seat	8.5 in / 216 mm
Product Weight	31 lb / 14.1 kg
Shipping Cube	9.5 ft³ / 0.27 m³

Contact sales representative for more information.

Features

- Conference chair with mesh backrest and upholstered seat
- Breathable mesh back promotes airflow
- Pneumatic seat height adjustment only
- Swivel tilt function for added comfort

MODELS: 8458S, 8459S

- Stools provide a unique desk-to-drafting seat height range

Options

- Chair frame is available in Asphalt or Alabaster
- Arm plastic matches frame color, as standard. Optional aluminum arms also available
- Available without arms (NA models)
- Back mesh is available in 10 colors: Berry, Black, Chalk, Charcoal, Citrus, Cobalt, Pool Blue, Sand, Shadow, Stone
- Base is standard in Black nylon. Also available in Polished Aluminium
- Carpet casters are standard. Hard surface casters are available

Construction (Seat)

- Plastic seat pan

Construction (Back)

- Fixed height fiberglass reinforced polymer frame



8459 Alabaster base/frame



8458NA Asphalt base/frame



8459NAS Alabaster base/frame



8458S Asphalt base/frame

Construction (Arms)
- Fixed height arms
- Fiberglass reinforced polymer
- Optional polished aluminium arms

Construction (Base)
- Injection molded nylon base; fiberglass reinforced
- 26 in (660 mm) diameter

Construction (Casters)
- 2.5 in (64 mm) hard (carpet) casters made of reinforced nylon
- Optional soft casters for hard floors are made of polyurethane coated nylon
- Dual wheel

Upholstery (Seat)
- Seat can be upholstered in fabric, vinyl or leather
- Front edge of seat is a seamless waterfall

Upholstery (Back)
- 100% polyester mesh back
- 100,000 double rubs

Foam
- High density molded foam seat cushion

Weight Capacity
Designed for an active weight capacity of 300 lb.

Warranty
Lifetime warranty on all components except the following:
- 5 year warranty on foam and textiles
- 12 year warranty on control mechanisms
- Warranty applies only to single shift, standard commercial usage (8 hours/day, 5 days/week)

Fire Rating
All textiles and foam is tested and certified, meeting California Technical Bulletin 117 (CAL TB 117-2013) standards.

Environmental
View Environmental Data Sheets online.
All foam is produced without using any ozone depleting chloro-flouro chemicals.

Awards/Certifications
- Meets or exceeds all applicable BIFMA standards for safety and durability
- Manufactured in ISO 9001 and 14001 certified facilities

Please visit globalfurnituregroup.com for additional product information including environmental certifications