spritz seating | product specification

Mesh Back Flip Seat Nesting Chairs
Models 6764, 6765

Dimensions

Overall Depth		23 in / 584 mm
Overall Width	6764	20.5 in / 521 mm
	6765	23.75 in / 603 mm
Overall Height		33 in / 838 mm
Seat Depth		17 in / 432 mm
Seat Width		18.5 in / 470 mm
Seat Height		17 in / 432 mm
Back Height - From Seat		16 in / 406 mm
Armrest Clearance	6764	no arms
	6765	20 in / 508 mm
Arm Height - From Seat	6764	no arms
	6765	8.5 in / 216 mm
Product Weight	6764	15 lb / 6.8 kg
	6765	16 lb / 7.3 kg
Shipping Cube	6764	11.25 ft³ / 0.32 m³
	6765	11.75 ft³ / 0.33 m³

Contact sales representative for more information.

Features
- Multi-purpose seating with flip up seat for nesting
- Translucent mesh back
- Four leg chairs
- When seat is flipped up for nesting, chair depth is 22 in (559 mm). Each additional nested chair adds only 8 in (203 mm) to depth

Options
- Mesh back is available four colors
- Frames is available in black or tungsten color
- Standard seat foam may be replaced with memory foam
- Chairs are available with casters on all four legs or on front

MODELS: 6764C, 6765C
- Carpet casters are standard. Hard surface casters are available (not available for front caster models)

Construction (Arms)
MODEL: 6765
- Fixed nylon cantilever arms

Construction (Seat)
- Polypropylene seat pan, 1 in (25 mm) thick

Construction (Frame)
- Metal tube frame, 0.875 in (22 mm) diameter

Construction (Glides)
- Black nylon glides



6764





6765C



6764FC

Construction (Casters)
- 2 in (50 mm) hard (carpet) casters made of reinforced nylon
- Optional soft casters for hard floors are made of polyurethane coated nylon
- Dual wheel

Upholstery (Seat)
- Seat can be upholstered in fabric, vinyl or leather
- Front edge of seat is a seamless waterfall

Upholstery (Back)
- Elastomeric mesh back
  - 49% Nylon
  - 30% Polyelastomer
  - 21% Polyester

Foam (Seat)
- High density molded seat foam

Weight Capacity
Designed for an active weight capacity of 300 lb.

Warranty
Lifetime warranty on all components except the following:
- 5 year warranty on foam and textiles
- 12 year warranty on control mechanisms
- Warranty applies only to single shift, standard commercial usage (8 hours/day, 5 days/week)

Fire Rating
All textiles and foam is tested and certified, meeting California Technical Bulletin 117 (CAL TB 117-2013) standards.

Environmental
View Environmental Data Sheets online. All foam is produced without using any ozone depleting chloro-flouro chemicals.

Awards/Certifications
- Meets or exceeds all applicable BIFMA standards for safety and durability
- Manufactured in ISO 9001 and 14001 certified facilities

Please visit globalfurnituregroup.com for additional product information including environmental certifications.