collingwood seating | product specification

Lounge Chairs
Models: GC36510, GC36511

Dimensions

Overall Depth	GC36510 GC36511	27.25 in / 692 mm 28.5 in / 724 mm
Overall Width		28 in / 711 mm
Overall Height	GC36510 GC36511	31 in / 787 mm 35.5 in / 902 mm
Seat Depth		19 in / 483 mm
Seat Width		21 in / 533 mm
Seat Height		18 in / 457 mm
Back Height - From Seat	GC36510 GC36511	12.5 in / 318 mm 17 in / 432 mm
Arm Height - From Seat		8 in / 203 mm
Product Weight		42-43 lbs. / 19.1-19.5 kg
Shipping Cube	GC36510 GC36511	19.25 ft³ / 0.54 m³ 22.5 ft³ / 0.64 m³

Contact sales representative for more information.

Features

- Four-leg chair
- Rounded back lounge seating with a residential look
- Cleanout at back of seat and impervious under seat layer for ease of cleaning

Options

- Glide options: non-marking glides (standard), felt glides, non-slip rubber glides or steel cushion glides
- Wood legs are available in Global's standard wood finishes
- Urethane legs are available in several finishes for increased durability and cleaning
- Available to be specified in two textiles: seat cushion separate from back/arm/front rail textile

COM Yardage

Yardage is based on unmatched materials with widths of 54 inches for seating.

MODEL: GC36510

- Full Unit: 4.50 yards
- Back: 3.25 yards
- Seat: 1.25 yards

MODEL: GC36511

- Full Unit: 5.00 yards
- Back: 3.75 yards
- Seat: 1.25 yards

Infection Control

- Sealed seams option (on seat and/or back)
- Moisture barrier liner option (on seat)
- Cleanout at back of seat
- Non-porous under seat layer
- Legs are replaceable on-site
- Seat is mechanically removable by an installer
- For proper cleaning and disinfecting practices, the textile selection needs to be identified. It is vital that following any chemical application a clear water wipe down occur to avoid chemical build up that will lead to deterioration of the textile. Contact Global should information on using a specific disinfectant be required

Construction (Seat and Back)

- Interlocking puzzle box construction
- Plywood seat frame, 1 in (25 mm) thick, 7-ply
- Synthetic woven webbing suspension system under seat
- Curved plywood back, 1 in (25 mm) thick, 7-ply



GC36510



GC36511

Construction (Legs)
- Legs taper slightly towards the floor
- All four legs are attached to chair frame using metal-to-metal connections
- High wood or urethane legs allow easy floor cleaning

Construction (Glides)
- Standard nylon glides
- Optional felt glides for sensitive flooring
- Optional non-slip rubber glides for hard surface
- Optional steel cushion glides for rubber or carpeted surfaces
- See glide matrix in Global Seating price list for recommended glides for various flooring types

Upholstery
- Chairs can be upholstered in fabric, coated textile or leather
- Available to be specified in two textiles: seat cushion separate from back/arm/front rail textile

Foam (Seat)
- 3.25 in (83 mm) thick Ultracell seat foam
- Density: 2.6 lbs., ILD: 35

Foam (Back)
- 0.75 in (19 mm) thick back foam
- Density: 1.9 lbs., ILD: 50

Weight Capacity
Designed for an active weight capacity of 350 lbs.

Warranty
Lifetime warranty on all components except the following:
- 5 year warranty on foam and textiles
- Warranty applies only to single shift, standard commercial usage (8 hours/day, 5 days/week)

Fire Rating
All textiles and foam is tested and certified, meeting California Technical Bulletin 117 (CAL TB 117-2013) standards.

Environmental
View Environmental Data Sheets online. All foam is produced without using any ozone depleting chloro-flouro chemicals.

Awards/Certifications
- Meets or exceeds all applicable BIFMA standards for safety and durability
- Manufactured in ISO 9001 and 14001 certified facilities

Please visit globalfurnituregroup.com for additional product information including industry and environmental certifications.