globalcare belong seating | product specification

Healthcare Bench and Ottomans
Models GC4251, GC4252, GC4253, GC4256 & GC4259

Bench Dimensions (Models GC4251, GC4252, GC4253 & GC4256)

Overall Depth		26.5 in / 673 mm
Overall Width	GC4251	24.75 in / 629 mm
	GC4252	47.75 in / 1213 mm
	GC4253 & GC4256	70.75 in / 1797 mm
Overall Height		18 in / 457 mm
Product Weight	GC4251	25 lbs / 11.4 kgs
	GC4252	45 lbs / 20.5 kgs
	GC4253	65 lbs / 29.5 kgs
	GC4256	60 lbs / 27.3 kgs
Shipping Cube	GC4251	13 ft³ / 0.37 m³
	GC4252	23 ft³ / 0.65 m³
	GC4253 & GC4256	33.25 ft³ / 0.94 m³

Ottoman Dimensions (Model GC4259)

Overall Depth	19 in / 483 mm
Overall Width	17.75 in / 451 mm
Overall Height	10.5 in / 267 mm
Product Weight	14 lbs / 6.4 kgs
Shipping Cube	3.6 ft³ / 0.10 m³

Contact sales representative for more information.

Features
- Designed for active and transient environments with rigorous demands
- All seating shipped fully assembled

MODELS GC4251, GC4252, GC4253 & GC4236
- Alternate models are available with linking brackets on left, right or both sides of seating. These allow installation of bridging tables or seats between two linking seating models (end tables are also available for linking to a single seating models)

Options
- Active fire barrier can be added
- Frame is standard in Tungsten. Also available in six other colours
- Frame can be weighted and made with tamperproof fasteners, for greater security
- For hard surface floors, non-marking glides are available

COM Yardage
Yardage is based on unmatched materials with widths of 54 inches for seating:

MODEL GC4251
- Total: 1.50 yards

MODEL GC4253
- Total: 3.00 yards

MODEL GC4252 & GC4256
- Total: 2.25 yards

MODEL GC4259
- Total: 1.00 yards

Infection Control
- No Velcro on seat
- Seam sealing option
- Moisture barrier option
- Seat cushions are removable and field replaceable
- For proper cleaning and disinfecting practices, the textile selection needs to be identified. It is vital that following any chemical application a clear water wipe down occur to avoid chemical build up that will lead to deterioration of the textile. Contact Global should information on using a specific disinfectant be required



GC4259



GC4253



GC4256

Construction (Overall Frame)
- Elliptical steel tube construction
- Welded frame with corner gussets

Construction (Seat)
- ⅝ in (16 mm) thick plywood seat frame, six-ply

Construction (Glides)
- Black injection molded polypropylene /polyethylene glides
- Non-marking glides also available for hard surfaces

Construction (Tables)
- Available on model GC4256 or bridge tables that connect to seating linking brackets
- High pressure laminate or thermally fused laminate table top

Upholstery
- Seat and back can be upholstered in fabric, vinyl or leather

Foam

MODELS GC4251, GC4252, GC4253 & GC4256
- 3.5 in (89 mm) thick Ultracell (high density) seat foam
- Density: 2.6 lbs, ILD: 35

MODEL GC4259
- 3 in (76 mm) thick Ultracell (high density) seat foam
- Density: 2.6 lbs, ILD: 35

Weight Capacity

Active weight capacity of 500 lbs per seat.

Warranty

10 year warranty on all components for 24 hour use except the following:
- Five year warranty on foams and fabrics

Fire Rating

All fabric and foam is tested and certified, meeting California Technical Bulletin 117 (CAL 117) standards.

Environmental

View Environmental Data Sheets online.
All foam is produced without using any ozone depleting chloro-flouro chemicals.

Awards/Certifications
- Meets or exceeds all applicable BIFMA standards for safety and durability
- Manufactured in ISO 9001 and 14001 certified facilities

Please visit globalfurnituregroup.com for additional product information including environmental certifications.