Desking & Tables
Models: SKWSRW####, SKWSRRT####, SKWSRLT####, SKWSRTRL####, SKWSRTBL####, SKWSRBTL####, SKWSCR####, SKWSCL####, SKWSRBR####, SKWSRBL####, SKWSRTR####, SKWSRTL####

Primary Surfaces Dimensions (Models: SKWSRW####, SKWSRRT####, SKWSRLT####, SKWSRTRL####, SKWSRTBL####, SKWSRBTL####, SKWSCR####, SKWSCL####)

Overall Depth	SKWSR_24##	24 in / 610 mm
	SKWSR_30##, SKWSC_30##	
	SKWSC_36##	30 in / 762 mm
		36 in / 914 mm
Overall Width	SKWSR_##60	60 in / 1524 mm
	SKWSR_##66	66 in / 1676 mm
	SKWSR_##72, SKWSC_##72	72 in / 1829 mm
	SKWSR_##78, SKWSC_##78	78 in / 1981 mm
	SKWSR_##84, SKWSC_##84	84 in / 2134 mm
	SKWSC_##96	96 in / 2438 mm
Overall Height	SKWS_####	1 in / 25 mm
Product Weight	SKWS_####	44.3-106.5 lbs. / 20.1-48.3 kg
Shipping Cube		0.83-2 ft³ / 0.024-0.057 m³

Return Surfaces Dimensions (Models: SKWSRBR####, SKWSRBL####, SKWSRR####. SKWSRL####, SKWSRTR####, SKWSRTL####)

Overall Depth	SKWSR_18##	18 in / 457 mm
Overall Width	SKWSR_##36	36 in / 914 mm
	SKWSR_##42	42 in / 1067 mm
	SKWSR_##48	48 in / 1219 mm
	SKWSR_##54	54 in / 1372 mm
	SKWSR_##60	60 in / 1524 mm
	SKWSR_##66	66 in / 1676 mm
Overall Height	SKWSR_####	1 in / 25 mm
Product Weight	SKWSR_####	20.1-37.2 lbs. / 9.1-16.9 kg
Shipping Cube		0.38-0.69 ft³ / 0.012-0.020 m³

Conferencing Tops Dimensions (Models: SKWSCT####, SKWSCW####, SKWSDW####)

Overall Depth	SKWS_30##	30 in / 762 mm
	SKWS_36##	36 in / 914 mm
Overall Width	SKWS_##72	72 in / 1829 mm
	SKWS_##78	78 in / 1981 mm
	SKWS_##84	84 in / 2134 mm
	SKWS_##96	96 in / 2438 mm
Overall Height	SKWSC_####	1 in / 25 mm
Product Weight	SKWSC_####	66.2-106.5 lbs. / 30.0-48.3 kg
Shipping Cube		1.25-2 ft³ / 0.035-0.057m³

Worksurface Support Column Kits Dimensions
Fixed Height Column Kits (Models: SKWSFH2C##T##, SKWSFH3C##T##)
Height Adjustable Column Kits (Models: SKWSHA2C##T##, SKWSHA3C##T##)

Overall Depth	SKWS_2C18T24, SKWS_3C18T24	6 in / 152 mm
Overall Width	SKWS_C##T##	20 in / 508 mm
Overall Height	SKWSFH_C##T##	28 in / 711 mm
	SKWSHA_C##T##	25-51.2 in / 635-1301 mm
Product Weight		81.3-122 lbs. / 36.9-55.3 kg
Shipping Cube		15.39-25.40 ft³ / 0.436-0.719 m³

Contact sales representative for more information.



SKWSRBL1842



SKWSRW2460



SKWSDW3072



SKWSFH2C30T36



SKWSHA2C30T36

Features
- 100% Canadian made
- 1 in (25 mm) thick high performance thermally fused laminate tops, HPL tops optional
- All worksurfaces to be supported by two or three column-fixed or height adjustable column kits, with one or two columns integrated with storage elements
- Tops shapes include
  - Rectangular, with optional one or two large radius corners (12 in / 305 mm radius on 24 in depth surfaces, 15 in / 381 mm radius on 30 in depth surfaces)
  - Racetrack and D-tops for conferencing applications
- Standard without grommets or cutouts for power modules
- If spans between leg column supports are greater than 48 in (1219 mm), worksurface support channels are required

Options
- Optional 1.0625 in (27 mm) thick high pressure laminate surfaces
- Available in a wide array of wood grain and solid color laminates
- Optional worksurface grommets or cutouts to accomodate in-surface power modules (power modules ordered separately); positions vary dependent on top size and configuration

Construction (Tops)
- 1 in (25 mm) thick tops constructed of 45 lbs. density particle board core, with top and bottom surface in thermally fused high performance laminate
- 1.0625 in (27 mm) thick high pressure laminate tops, primary surface finished in high pressure laminate, 45 lb density particle board core with bottom surface finished in kraft paper backing
- Edges are finished with 0.12 in (3 mm) thick PVC edge banding

Worksurface Support, Column Kits
- Fixed Height Column Kits
  - 28 in (711 mm) overall height with 2.75 in (70 mm) diameter aluminum column and a 20 in (508 mm) long, 6 in (29 mm) high aluminum die cast foot
  - Standard with leveling glides
  - Column kits are finished in a highly durable powder coat process
  - Available in an array of standard finishes
- Height Adjustable Column Kits
  - Available in two and three column configurations, must be specified in conjunction with integrated storage
  - 120 V
  - 2.75 (70 mm) diameter leg columns
  - 180 lbs. (81.6 kg) lift capacity per column
  - 0.7 in (18 mm) glide adjustment range
  - Travels 35 mm per second
  - Noise level <50 dB
  - Three prong plug with 39.3 in (1 m) cord
  - Available in an array of standard finishes

Warranty
Lifetime warranty on all components.

Environmental
View Environmental Data Sheet online.

Awards/Certifications
- Meets or exceeds all applicable ANSI/BIFMA X5.9-2019, X5.5-2021 standards for safety and durability
- Greenguard and Greenguard Gold
- TSCA Title VI compliant
- ANSI/BIFMA e3-2019 LevelTM3 certified
- Manufactured in ISO 9001 and 14001 certified facilities

Please visit globalfurnituregroup.com for additional product information including environmental certifications