Low Storage

Low Storage without Leg Grommets
Models: SKSLOS20##, SKSLFD20##, SKSLBB20##, SKSLHD20##, SKSLCHL(R/L)20##, SKSLCHD(R/L)20##, SKSLCOL(R/L)20##, SKSLCOD(R/L)20##, SKSLCFF20##

Low Storage with One Leg Grommet
Models: SKSLHDG20##, SKSLCHO(R/L)20##, SKSLCHF(R/L)20##, SKSLCHB(R/L)20##, SKSLCHOF(R/L)20##, SKSLCHOEF(R/L)20##, SKSLCHOD(R/L)20##, SKSLCHOED(R/L)20##, SKSLCOHO20##, SKSLCHBF(R/L)20##, SKSLCHOBF(R/L)20##, SKSLCHDG20##

Low Storage with Two Leg Grommets
Models: SKSLCHFH20##, SKSLCHBH20##, SKSLCHOH20##, SKSLHOFHR20##, SKSLCHOFHL20##, SKSLCHOBH(R/L)20##, SKSLCHOBFH(R/L)20##, SKSLCHBFH(R/L)20##



SKSLCHDG2072

Low Storage Dimensions

Overall Depth	SKSL_20##	20 in / 508 mm
Overall Width	SKSL_2024	24 in / 610 mm
	SKSL_2030	30 in / 762 mm
	SKSL_2036	36 in / 914 mm
	SKSL_2042	42 in / 1067 mm
	SKSL_2048	48 in / 1219 mm
	SKSL_2054	54 in / 1372 mm
	SKSL_2060	60 in / 1524 mm
	SKSL_2066	66 in / 1676 mm
	SKSL_2072	72 in / 1829 mm
	SKSL_2078	78 in / 1981 mm
	SKSL_2084	84 in / 2134 mm
Overall Height	SKSL_20##	14 in / 356 mm
Product Weight	SKSL_20##	58.3-223.7 lbs. / 26.4-101.5 kg
Shipping Cube		2.92-13.17 ft³ / 0.083-0.373 m³

Contact sales representative for more information.



SKSLCHODR2066



SKSLCHOBHR2078

Features

- 1 in (25 mm) thick high performance thermally fused laminate tops
- Top overlay construction, 1 in (25 mm) thick side and bottom panels, 0.75 in (19 mm) thick back panel, drawer and/or door fronts
- 24 in (610 mm) to 30 in (762 mm) wide low storage to be supported by SKSLL low storage legs, or combined with other low or high storage to be supported by SKSLU steel storage undercarriage
- Die cast D-shaped profile aluminum legs are 1.575 in (40 mm) by 1.4 in (36 mm)
- 36 in (914 mm) and wider units are to be supported by the same width SKSLU storage undercarriage, or combined with other low or high storage to be supported by corresponding SKSLU storage undercarriage
- Die cast aluminum handles where applicable, are 8 in (203 mm) wide with 7.56 in (192 mm) center-to-center drilling
- Box and file drawers are equipped with premium full extension ball bearing drawer slides
- Adjustable shelves, where available, are 0.75 in (19 mm) thick and have three adjustable positions in 1.26 in (32 mm) increments
- Hinged doors are equipped with soft close 103° overlay hinges
- Oval cut out(s) for column kits, when applicable, are 7.5 in (191 mm) by 4.5 in (114 mm)
- Drawers and doors are all locking
- 20 in (508 mm) deep upholstered cushions are available to fit atop low storage units, available in widths to suit low storage options

Options

- An array of standard wood grain or solid laminate finishes are available for tops, chassis and doors/drawers
- Select top, top edge, chassis, and door/drawer finishes are selected separately
- Door and drawer handles, SKSLL and SKSLU storage support are available in a broad range of highly durable metal powder coat paint finishes

Construction

- All low storage are 14 in (356 mm) high by 20 in (508 mm) deep, in widths ranging from 24 in (610 mm) to 84 in (2134 mm)
- 1 in (25 mm) thick high performance thermally fused laminate tops with 0.12 in (3 mm) thick PVC edge banding
- Chassis sides and bottom are 1 in (25 mm) thick, back panel is 0.75 in (19 mm) thick high performance thermally fused laminate

Warranty

Lifetime warranty on all components.

Environmental

View Environmental Data Sheet online.

Awards/Certifications

- Meets or exceeds all applicable ANSI/BIFMA X5.9-2019, X5.5-2021 standards for safety and durability
- Greenguard and Greenguard Gold
- TSCA Title VI compliant
- ANSI/BIFMA e3-2019 LevelTM3 certified
- Manufactured in ISO 9001 and 14001 certified facilities

Please visit globalfurnituregroup.com for additional product information including environmental certifications.