ATWPOP28 | application typical | Bridges II

Bill of materials

12-9-2025

Line	Cat	Qty	Part Number		
1	GUS	5	**5541**	Ext Weight (lbs)	180.00
			FACTOR, Mesh Back, Medium Back, Task Basic Swivel, Std Fixed Arms, Std Molded Black Base, Std 2" Dual Wheel Carpet Casters,	Ext Volume (Ft3)	52.50
2	GCU	4	**BRT25BF24C**	Ext Weight (lbs)	296.00
			24"d x 15.5"w x 25"h, Box/File Pedestal w/ Casters, Handles, Locking, BRIDGES II	Ext Volume (Ft3)	20.08
3	GCU	1	**BRTAGDD60**	Ext Weight (lbs)	21.00
			57"w x 16"h x .25"d, Glass Table Divider, Secures Between Back to Back Tables, 15.7" Above Surface, Includes 2 Support Brackets,	Ext Volume (Ft3)	0.13
4	GCU	2	**BRTAGDD66**	Ext Weight (lbs)	46.00
			63"w x 16"h x .25"d, Glass Table Divider, Secures Between Back to Back Tables, 15.7" Above Surface, Includes 2 Support Brackets,	Ext Volume (Ft3)	0.28
5	GCU	2	**BRTBA63L**	Ext Weight (lbs)	26.00
			62.5"d x 28"h, Back to Back Rect. Leg Assembly w/ Levelers, Can be Shared by Adjoining Worksurfaces, BRIDGES II	Ext Volume (Ft3)	6.42
6	GCU	2	**BRTE8D1**	Ext Weight (lbs)	0.20
			Circuit #1, Black, Utility Circuit, Snaps into Power Distribution Housing, Up to 13 Duplex Receptacles per Circuit, BRIDGES	Ext Volume (Ft3)	2.00
7	GCU	3	**BRTE8D2**	Ext Weight (lbs)	0.30
			Circuit #2, Black, Utility Circuit, Snaps into Power Distribution Housing, Up to 13 Duplex Receptacles per Circuit, BRIDGES	Ext Volume (Ft3)	3.00
8	GCU	2	**BRTE8DA**	Ext Weight (lbs)	0.20
			Circuit A, Black, Dedicated Circuit, Snaps into Power Distribution Housing, Up to 13 Duplex Receptacles per Circuit, BRIDGES	Ext Volume (Ft3)	2.00
9	GCU	3	**BRTE8DB**	Ext Weight (lbs)	0.30
			Circuit B, Black, Dedicated Circuit, Snaps into Power Distribution Housing, Up to 13 Duplex Receptacles per Circuit, BRIDGES	Ext Volume (Ft3)	3.00
10	GCU	1	**BRTEBF**	Ext Weight (lbs)	4.00
			72"Long, Basefeed, Single Power Entry from Floor or Wall Located Building Power Supply, Connects to Power Distribution Housing,	Ext Volume (Ft3)	2.00
11	GCU	1	**BRTEETB60SKIT**	Ext Weight (lbs)	8.00
			54.34"w x 11.6"d x 2.5"h, Below Worksurface Single Power/Data Trough, Includes 1 Power Housing, Mounting Brackets, 1 Data Cable	Ext Volume (Ft3)	0.91
12	GCU	2	**BRTEETB66DKIT**	Ext Weight (lbs)	15.00
			60.3"w x 8.5"d x 2.5"h, Below Worksurface Double Power/Data Trough, Includes 1 Power Housing, Mounting Brackets, 1 Data Cable	Ext Volume (Ft3)	1.48
13	GCU	2	**BRTEHH28**	Ext Weight (lbs)	2.00
			28" - Housing to Housing Pass-Thru Cable, BRIDGES II POWER BEAM	Ext Volume (Ft3)	2.34
14	GCU	4	**BRTSB66C**	Ext Weight (lbs)	24.36
			61"w x 2"h, Universal Beam, Use for End of Run, Interconnecting, Single and Back to Back Table Applications, Includes Adjustable	Ext Volume (Ft3)	32.00
15	GCU	1	**BRTSINT60S**	Ext Weight (lbs)	155.00
			24"d x 60"w x 29"h, Fully Upholstered Integrated Armless Single Seat w/ Backrest, Metal Base, Only Compatible w/ Back to Back	Ext Volume (Ft3)	24.17
16	GCU	2	**BRTTES63**	Ext Weight (lbs)	136.00
			15.5"d x 62.5"w x 15"h, Table Mounted End Shelf, Secures to the End of a Single or Back to Back Table, Internal Height 13.25"h,	Ext Volume (Ft3)	16.80

ATWPOP28 | application typical | Bridges II

Bill of materials

12-9-2025

Line	Cat	Qty	Part Number		
17	GCU	4	**BRTWSA3066**	Ext Weight (lbs)	216.00
			30"d x 66"w x 1"h, Rectangular Worksurface 1 w/ Anodized Aluminum Access Door, BRIDGES II	Ext Volume (Ft3)	7.20
18	GCU	1	**GRB28**	Ext Weight (lbs)	100.00
			28" Dia x 28"h, Round Base, Seated Height, Plate Base w/ 3" Dia x 27.5"h Column, Fully Assembled, 1/2" Adj. Glides, Use w/ Either	Ext Volume (Ft3)	15.63
19	GCU	1	**GRBTP42**	Ext Weight (lbs)	44.00
			42" Dia x 1"h, TFL, Flat Edge, Round, Top Only, 1 Base Required, Use w/ GRB28 or GSB23 Base, SWAP, TABLES	Ext Volume (Ft3)	2.50
20	GUS	2	**R5APPC**	Ext Weight (lbs)	27.00
			REBOUND, Armchair, Polypropylene Seat & Back, Std 4 Legged Base, Casters, Stack 5 High on Floor, 10 High on Dolly, GLOBAL	Ext Volume (Ft3)	15.26