ATWPOP154 | application typical | Bridges II

Bill of materials

12-9-2025

Line	Cat	Qty	Part Number		
1	GUS	4	**5541**	Ext Weight (lbs)	144.00
			FACTOR, Mesh Back, Medium Back, Task Basic Swivel, Std Fixed Arms, Std Molded Black Base, Std 2" Dual Wheel Carpet Casters,	Ext Volume (Ft3)	42.00
2	GCU	8	**BHBF01**	Ext Weight (lbs)	4.00
			4"d x 3"w x 0.1"h, Flat Bracket, Used to ensure alignment of neighboring worksurfaces, BRIDGES II	Ext Volume (Ft3)	8.00
3	GCU	2	**BRT21GDS8416**	Ext Weight (lbs)	392.00
			16"d x 84"w x 21"h, Table Supported Double Sided Storage w/ 1 Sliding Glass Door, Cannot be used in Conjunction w/ Above	Ext Volume (Ft3)	42.00
4	GCU	1	**BRTBAR4PDA2484L**	Ext Weight (lbs)	272.00
			50.5"d x 84"w x 29"h, 4 Person Back-2-Back Package, Rectangular Legs w/ Levelers, Split Access Doors, BRIDGES II	Ext Volume (Ft3)	15.66
5	GCU	2	**BRTE8D1**	Ext Weight (lbs)	0.20
			Circuit #1, Black, Utility Circuit, Snaps into Power Distribution Housing, Up to 13 Duplex Receptacles per Circuit, BRIDGES	Ext Volume (Ft3)	2.00
6	GCU	2	**BRTE8D2**	Ext Weight (lbs)	0.20
			Circuit #2, Black, Utility Circuit, Snaps into Power Distribution Housing, Up to 13 Duplex Receptacles per Circuit, BRIDGES	Ext Volume (Ft3)	2.00
7	GCU	2	**BRTE8DA**	Ext Weight (lbs)	0.20
			Circuit A, Black, Dedicated Circuit, Snaps into Power Distribution Housing, Up to 13 Duplex Receptacles per Circuit, BRIDGES	Ext Volume (Ft3)	2.00
8	GCU	2	**BRTE8DB**	Ext Weight (lbs)	0.20
			Circuit B, Black, Dedicated Circuit, Snaps into Power Distribution Housing, Up to 13 Duplex Receptacles per Circuit, BRIDGES	Ext Volume (Ft3)	2.00
9	GCU	1	**BRTEBF**	Ext Weight (lbs)	4.00
			72"Long, Basefeed, Single Power Entry from Floor or Wall Located Building Power Supply, Connects to Power Distribution Housing,	Ext Volume (Ft3)	2.00
10	GCU	2	**BRTEETB84DKIT**	Ext Weight (lbs)	19.60
			78.3"w x 8.5"d x 2.5"h, Below Worksurface Double Power/Data Trough, Includes 2 Power Housing, Mounting Brackets, 2 Data Cable	Ext Volume (Ft3)	1.92
11	GCU	1	**BRTEHH28**	Ext Weight (lbs)	1.00
			28" - Housing to Housing Pass-Thru Cable, BRIDGES II POWER BEAM	Ext Volume (Ft3)	1.17
12	GCU	4	**BRTMLD60**	Ext Weight (lbs)	240.00
			57"w x 30"h x 1.25"d, Table Mounted Framed Laminate Divider, 2 Support Brackets, Use with Single Sided Tables, BRIDGES II	Ext Volume (Ft3)	11.88
13	GCU	4	**BRTPEG24H21**	Ext Weight (lbs)	36.00
			24"w x 20.5"h x .75"d, Perpendicular Laminate End of Run Gable, Secures to the Side of Table Inbetween Rectangular Legs Only,	Ext Volume (Ft3)	0.84
14	GCU	4	**BRTSL24L**	Ext Weight (lbs)	32.00
			24"d x 28"h, Single Rect. Leg Assembly w/ Levelers, 2 Legs w/ a Beam create a Single Table,1 Leg can be shared at seam - BRIDGES	Ext Volume (Ft3)	5.36
15	GCU	4	**BRTTB60C**	Ext Weight (lbs)	31.00
			72.5"w x 2"h, Telescopic Beam, Provides Support For a Worksurface Connected Perpendicularly to Primary Tables, BRIDGES II	Ext Volume (Ft3)	32.00
16	GCU	4	**BRTWS2460**	Ext Weight (lbs)	156.00
			24"d x 60"w x 1"h, Rectangular Worksurface, BRIDGES II	Ext Volume (Ft3)	5.20

ATWPOP154 | application typical | Bridges II

Bill of materials

12-9-2025

Line	Cat	Qty	Part Number		
17	GCU	4	**GAMCSSDE**	Ext Weight (lbs)	30.00
			Single Screen Double Extension Arm, Displays Tilt and Swing 180 degrees, Use on Bridge II Product Only, BRIDGES II	Ext Volume (Ft3)	4.36