ATWPOP156 | application typical | Bridges II

Bill of materials

12-9-2025

Line	Cat	Qty	Part Number		
1	GUS	6	**5541**	Ext Weight (lbs)	216.00
			FACTOR, Mesh Back, Medium Back, Task Basic Swivel, Std Fixed Arms, Std Molded Black Base, Std 2" Dual Wheel Carpet Casters,	Ext Volume (Ft3)	63.00
2	GCU	2	**BRTAGDD72**	Ext Weight (lbs)	50.00
			69"w x 16"h x .25"d, Glass Table Divider, Secures Between Back to Back Tables, 15.7" Above Surface, Includes 2 Support Brackets,	Ext Volume (Ft3)	0.32
3	GCU	2	**BRTBA34L**	Ext Weight (lbs)	20.00
			34"d x 28"h, Back to Back Rect. Leg Assembly w/ Levelers, Can be Shared by Adjoining Worksurfaces, BRIDGES II	Ext Volume (Ft3)	4.94
4	GCU	2	**BRTBA51L**	Ext Weight (lbs)	24.00
			50.5"d x 28"h, Back to Back Rect. Leg Assembly w/ Levelers, Can be Shared by Adjoining Worksurfaces, BRIDGES II	Ext Volume (Ft3)	5.92
5	GCU	3	**BRTE8D1**	Ext Weight (lbs)	0.30
			Circuit #1, Black, Utility Circuit, Snaps into Power Distribution Housing, Up to 13 Duplex Receptacles per Circuit, BRIDGES	Ext Volume (Ft3)	3.00
6	GCU	3	**BRTE8D2**	Ext Weight (lbs)	0.30
			Circuit #2, Black, Utility Circuit, Snaps into Power Distribution Housing, Up to 13 Duplex Receptacles per Circuit, BRIDGES	Ext Volume (Ft3)	3.00
7	GCU	3	**BRTE8DA**	Ext Weight (lbs)	0.30
			Circuit A, Black, Dedicated Circuit, Snaps into Power Distribution Housing, Up to 13 Duplex Receptacles per Circuit, BRIDGES	Ext Volume (Ft3)	3.00
8	GCU	3	**BRTE8DB**	Ext Weight (lbs)	0.30
			Circuit B, Black, Dedicated Circuit, Snaps into Power Distribution Housing, Up to 13 Duplex Receptacles per Circuit, BRIDGES	Ext Volume (Ft3)	3.00
9	GCU	1	**BRTEBF**	Ext Weight (lbs)	4.00
			72"Long, Basefeed, Single Power Entry from Floor or Wall Located Building Power Supply, Connects to Power Distribution Housing,	Ext Volume (Ft3)	2.00
10	GCU	2	**BRTEETB72DKIT**	Ext Weight (lbs)	16.60
			66.3"w x 8.5"d x 2.5"h, Below Worksurface Double Power/Data Trough, Includes 1 Power Housing, Mounting Brackets, 1 Data Cable	Ext Volume (Ft3)	1.62
11	GCU	4	**BRTSB72C**	Ext Weight (lbs)	26.96
			67"w x 2"h, Universal Beam, Use for End of Run, Interconnecting, Single and Back to Back Table Applications, Includes Adjustable	Ext Volume (Ft3)	36.00
12	GCU	4	**BRTWSAA2472**	Ext Weight (lbs)	172.00
			24"d x 72"w x 1"h, Rectangular Worksurface w/ 2 Anodized Aluminum Access Doors, BRIDGES II	Ext Volume (Ft3)	5.64
13	GCU	2	**BWATMGD72**	Ext Weight (lbs)	56.00
			57"w x 21.5"h x .25"d, Glass Table Divider, 3 Support Brackets, Secures Between Back to Back Tables, FREEFIT	Ext Volume (Ft3)	4.26
14	GCU	1	**FT54BLFNL**	Ext Weight (lbs)	123.00
			2 Stage Column, Back to Back, Height Adjustable Programmable Base Only, Long Framed used w/66"w and 72"w Tops (Tops Sold	Ext Volume (Ft3)	2.94
15	GCU	1	**FTB2B72KITNB**	Ext Weight (lbs)	3.50
			72" Back to Back Trough Kit, Includes Back to Back Trough, 2 Under Surface Wire Managements and 2 Cable Chains, FREEFIT Benching	Ext Volume (Ft3)	0.30
16	GCU	2	**FTTABRC**	Ext Weight (lbs)	4.80
			FreeFit Benching to Bridges Connector, Connects FreeFit Benching Back to Back to 29"H Bridges Below Worksurface Power Trough,	Ext Volume (Ft3)	0.56

ATWPOP156 | application typical | Bridges II

Bill of materials

12-9-2025

Line	Cat	Qty	Part Number		
17	GCU	2	**FTWR2370**	Ext Weight (lbs)	96.00
			23"d x 70"w x 1"h, Height Adjustable Rectangular Worksurface, Base Sold Separately, FREEFIT BENCHING	Ext Volume (Ft3)	7.60