Backboards
Models: SKBB####, SKBBR####, SKBBL####, SKBBC####, SKBS####, SKBD####, SKBOS####

Backboards Dimensions

Overall Depth	SKB_####	2 in / 50 mm
Overall Width	SKB_##36	36 in / 914 mm
	SKB_##42	42 in / 1067 mm
	SKB_##48	48 in / 1219 mm
	SKB_##54	54 in / 1372 mm
	SKB_##60	60 in / 1524 mm
	SKB_##66	66 in / 1676 mm
	SKB_##72	72 in / 1829 mm
	SKB_##78	78 in / 1981 mm
	SKB_##84	84 in / 2134 mm
Overall Height	SKBB_34##	34 in / 864 mm
	SKBB_40## SKBS40##	40 in / 1016 mm
	SKBB_46## SKBS46##	46 in / 1168 mm
	SKBB_52## SKBS52##	52 in / 1321 mm
	SKBB_58## SKBS58##	58 in / 1473 mm
	SKBOS40##	26 in / 660 mm
	SKBOS46##	32 in / 813 mm
	SKBOS52##	38 in / 965 mm
	SKBOS58##	44 in / 1118 mm
Product Weight	SKB_####	37.9-207.3 lbs. / 17.2-94.0 kg
Shipping Cube		1.67-31.01 ft³ / 0.047-0.878 m³

Contact sales representative for more information.

SKBOS4066

SKBB3436

SKBB4060

SKBB4672

SKBB5284

Features

- Available in 0.75 in (19 mm) thick high performance thermally fused laminate or dry erase material, and 1.1 in (28 mm) thick PET Felt surfaces
- Units are wall mounted (mounting rails included, fasteners to affix to wall not included)
- When specified with thermally fused laminate, backboards have 0.12 in (3 mm) thick corresponding PVC finish edge banding
- When wood grain laminate finish is selected, grain pattern will run horizontally
- Backboards, when specified with PET Felt surface (0.35 in/9 mm thick), are bonded to thermally fused laminate backboard
- Patterned PET Felt is available featuring vertical V grooves routed into the PET Felt material
- Backboards with shelves are available with PET Felt below shelving

MODELS: SKBB####, SKBS####

- When mounted, units should be flush with the top of the low storage and aligned with the top of the high storage

MODEL: SKBOS####

- When mounted, unit will fill void between the top of the low storage and the bottom of the wall-mounted overheads

MODEL: SKBS####

- For units with one shelf, shelf is 10 in (254 mm) deep and fixed 14 in (356 mm) from top of backboard

MODEL: SKBD####

- For units with two shelves, shelves are 10 in (254 mm) deep, top shelf is fixed 14 in (356 mm) fixed from top of backboard, with 14 in (356 mm) clearance between shelves
- Not for use with above height adjustable worksurfaces

Options

- Thermally fused laminate available in a wide array of wood grain and solid color laminates
- PET Felt available in 18 standard colors
- Backboards available with square corners, or optional one or two 6 in (152 mm) radius corners
- Patterned PET Felt options
  - Equal Spacing: spacing between routed V grooves, center-to-center, is 3 in (76 mm)
  - Asymmetrical: pattern repeats every 15 in (381 mm). Spacing between V grooves, center-to-center in a vertical strip, is 1.5 in (38 mm) + 3 in (76 mm) + 4.5 in (114 mm) + 6 in (152 mm)

Construction

- Thermally fused laminate backboards are 0.75 in (19 mm) thick tops constructed of 45 lbs. density particle board core with corresponding 0.12 in (3 mm) thick PVC edge banding
- Dry erase surface backboards are 0.75 in (19 mm) thick, constructed of high pressure laminate surface bonded to 45 lbs. density particle board core with corresponding 0.12 in (3 mm) thick PVC edge banding in Designer White
- Backboards with PET Felt surfaces are 2 in (50 mm) thick overall, constructed of 0.35 in (9 mm) thick PET felt adhered to 0.75 in (19 mm) thick thermally fused laminate with corresponding 0.12 in (3 mm) thick PVC edge banding
- Mounting rails included, extruded aluminum is 100% recyclable

Warranty

Lifetime warranty on all components.

Environmental

View Environmental Data Sheet online.

Awards/Certifications

- Meets or exceeds all applicable ANSI/BIFMA X5.9-2019, X5.5-2021 standards for safety and durability
- Greenguard and Greenguard Gold
- TSCA Title VI compliant
- ANSI/BIFMA e3-2019 LevelTM3 certified
- Manufactured in ISO 9001 and 14001 certified facilities

Please visit globalfurnituregroup.com for additional product information including industry and environmental certifications.