# **ATWPOP230** | application typical | Evolve Power Beam

## Bill of materials

**04-07-2026**

| Line | Cat | Qty | Part Number | | |
|---|---|---|---|---|---|
| 1 | GCU | 4 | **BRTMFD54** | Ext Weight (lbs) | 0.00 |
| | | | 51"w x 30"h x 1.25"d, Table Mounted Framed Tackable Fabric Divider, 2 Support Brackets, Use with Single Sided Tables, BRIDGES | Ext Volume (Ft3) | 0.00 |
| 2 | EFG | 4 | **EVCUSHION15X18X2** | Ext Weight (lbs) | 8.00 |
| | | | 15"w x 18"d x 2"h, Pedestal Seat Cushion, PRIME | Ext Volume (Ft3) | 1.32 |
| 3 | EPB | 1 | **EVE8CP18** | Ext Weight (lbs) | 0.95 |
| | | | 18" - Flexible Mesh Jumper Cable, Used to Connect 2 Power Distrubution Housings Separated by Post | Ext Volume (Ft3) | 0.46 |
| 4 | EPB | 1 | **EVE8FR3PB** | Ext Weight (lbs) | 0.00 |
| | | | 84" Long, Power Beam Basefeed Power Entry, Flexible Vinyl Conduit, Snaps to Power Distribution Housing, Includes Bracket to | Ext Volume (Ft3) | 0.00 |
| 5 | EPB | 2 | **EVE8PD60** | Ext Weight (lbs) | 3.60 |
| | | | 60", Power Distribution Housing | Ext Volume (Ft3) | 2.40 |
| 6 | EPB | 2 | **EVE8RD1** | Ext Weight (lbs) | 0.22 |
| | | | #1 Utility Circuit, Duplex Receptacle, Black, Use an I-Connector w/ Duplex to allow for an additional Duplex in 66"w and 72"w Raceway | Ext Volume (Ft3) | 0.10 |
| 7 | EPB | 2 | **EVE8RD2** | Ext Weight (lbs) | 0.22 |
| | | | #2 Utility Circuit, Duplex Receptacle, Black, Use an I-Connector w/ Duplex to allow for an additional Duplex in 66"w and 72"w Raceway | Ext Volume (Ft3) | 0.10 |
| 8 | EPB | 2 | **EVE8RDA** | Ext Weight (lbs) | 0.22 |
| | | | A, Dedicated Circuit, Duplex Receptacle, Black, Use an I-Connector w/ Duplex to allow for an additional Duplex in 66"w and 72"w | Ext Volume (Ft3) | 0.10 |
| 9 | EPB | 2 | **EVE8RDB** | Ext Weight (lbs) | 0.22 |
| | | | B, Dedicated Circuit, Duplex Receptacle, Black, Use an I-Connector w/ Duplex to allow for an additional Duplex in 66"w and 72"w | Ext Volume (Ft3) | 0.10 |
| 10 | EPB | 1 | **EVPB60** | Ext Weight (lbs) | 0.00 |
| | | | 6"h x 60"w, Power Beam Raceway w/o Electrical Cut Out for Basefeed, 3 Knockouts, Aluminum Top Cap, Aluminum Bottom Trim, | Ext Volume (Ft3) | 0.00 |
| 11 | EPB | 1 | **EVPBE60** | Ext Weight (lbs) | 0.00 |
| | | | 6"h x 60"w, Power Beam Raceway w/ Electrical Cut Out for Basefeed, 3 Knockouts, Aluminum Top Cap, Shortened Aluminum | Ext Volume (Ft3) | 0.00 |
| 12 | EPB | 1 | **EVPBFCL24** | Ext Weight (lbs) | 0.00 |
| | | | 24"h x 6"w x 18"d, Vertical Cover for Basefeed w/ T-Leg Connector, Connects to Power Beam Raceway w/ Electrical Cut Out, End of Run | Ext Volume (Ft3) | 0.00 |
| 13 | EPB | 1 | **EVPBGICB24** | Ext Weight (lbs) | 0.00 |
| | | | 24"h x 2"w, Post Leg Connector w/ Adjustable Glide, Use In Conjunction w/ T-Leg Connectors | Ext Volume (Ft3) | 0.00 |
| 14 | EPB | 1 | **EVPBL24** | Ext Weight (lbs) | 0.00 |
| | | | 24"h x 18"w, T-Leg Connector w/ Adjustable Glides, Use Throughout Power Beam Span for Stability | Ext Volume (Ft3) | 0.00 |
| 15 | EPB | 2 | **EVPBLEP2463** | Ext Weight (lbs) | 0.00 |
| | | | 24"h x 63"w, Laminate End Panel, Attaches to Power Beam Connector w/ T-Leg, Includes Bracket to Attached to T-Leg | Ext Volume (Ft3) | 0.00 |
| 16 | EPB | 2 | **EVPBLERT24** | Ext Weight (lbs) | 0.00 |
| | | | 21.4"h, End of Run Aluminum Trim for Connector Legs | Ext Volume (Ft3) | 0.00 |

# **ATWPOP230** | application typical | Evolve Power Beam

## Bill of materials

**04-07-2026**

| Line | Cat | Qty | Part Number | | |
|---|---|---|---|---|---|
| *17* | GCU | 4 | **FT52SF24** | Ext Weight (lbs) | 0.00 |
| | | | 24"d, 2 Stage Column, Height Adjustable Base Only, Short Frame used/w 46"w - 58"w Tops, (Tops Sold Separate), FREEFIT, | Ext Volume (Ft3) | 0.00 |
| *18* | GCU | 4 | **FTWR2358** | Ext Weight (lbs) | 0.00 |
| | | | 23"d x 58"w x 1"h, Height Adjustable Rectangular Worksurface, Base Sold Separately, FREEFIT BENCHING | Ext Volume (Ft3) | 0.00 |
| *19* | EFG | 4 | **UUPW0BF18P** | Ext Weight (lbs) | 294.00 |
| | | | 18"d x 15"w x 23.3"h, Box/File Mobile Pedestal, Full Pull, PRIME | Ext Volume (Ft3) | 18.40 |